

Torque anchor

The easy operation and a perfect stability of these anchors is proofed in many application in different fields.

The 3 blocks will be anchored in the inner wall of the casing, supported by internal elastic elements

Suitable for torque up to 3000Nm, with excellent corrosion resistance in contact with H₂S, CO₂ and aromatic hydrocarbon as well.

Easy to use, safe and reliable

Technical parameters

as follows, connecting threads (API standard), can also be according to customers special demand

Model	Casing OD	Fit		EUE Link Thread	
		Range [mm]	Range [inch]	Top-side thread	End-side Thread
512	5 1/2"	120-128	4.72-5.03	3 1/2"	2 7/8"
658/2	6 5/8"	146-154	5.75-6.06	2 7/8"	2 7/8"
658/3	6 5/8"	146-154	5.75-6.06	3 1/2"	3 1/2"
700	7"	156-163	6.14-6.41	3 1/2"	3 1/2"
958	9 5/8"	192-224	7.55-7.87	3 1/2"	2 7/8"



TORQUE ANCHORS

Size	Casing \varnothing [mm / inch]	Tube Weight [kg/meter lb/ft]	Tool OD [mm / inch]	Connection tread [mm / inch]	Minor \varnothing [mm / inch]
A	140 5 - 1/2"	20 - 30 14 - 22	120 4,72"	72,9 2 - 7/8"	61 2,4"
B	178 7"	25 - 40 18 - 27	156 6,14"	88,9 3 - 1/2"	74 2,9"
C	219 8 - 5/8"	31 - 50 21 - 34	198 7,8"	114,3 4 - 1/2"	100 3,94"
D	245 9 - 5/8"	45 - 72 30 - 50	217 8,5"	114,3 4 - 1/2"	100 3,94"

